

4 INCH THERMAL LABEL PRINTER

Model: **KD4600**

FEATURES

- Compatible with mobile devices including iOS, Android, and Windows
- 152mm/s high speed printing
- Support 8MB Flash Memory and 8MB SDRAM
- No carbon ribbon, no ribbon, no ink



High definition
printing



Self-inspection



Error alert



Big font



High printing
speed



Rotating
screen



TECHNICAL SPECIFICATIONS

MODEL	
Model	KD4600
Print Method	Direct Thermal
Resolution	203dpi (8 dots/mm)
Printing Width	108mm
Interface	U/U+BT
Print Speed	152 mm/s max

FONTS	
Font A	12x24
Font B	9x17
Chinese	GB18030, BIG5 24x24dots
Japanese/Korea	Optional
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software

BARCODE	
1D	Code 39, Code 93, Code 128UCC, Code 128, subsets A/B/C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC (2/5 digits add-on), MSI, PLESSEY, POSTNET, China POST
2D	PDF-417, Maxicode, DataMatrix, QR code

POWER SUPPLY	
Input	AC 100V-240V 50/60HZ
Output	DC 24V / 2.5A

DETECTION	
Sensors	Thermal sensitive resistance
Paper exists detection	Photoelectric sensor

PAPER	
Paper Type	Thermal Label Paper
Paper Width	118mm
Paper Thickness	0.06-0.25mm
Roll inner Diameter	Max. Ø110 mm
Paper off	Tear off

PHYSICAL CHARACTERISTICS	
Working Condition	5-40°C (41-104°F), Humidity 25-85% non-condensing
Storage Condition	-40-60°C (-41-140°F), Humidity 10-90% non-condensing
Dimensions	224(D) x 180(W) x 161(H) mm
Net weight	1.45kg

PERFORMANCE FEATURES	
Processor	32-bit CPU
Memory	8MB Flash Memory / 8MB SDRAM

RELIABILITY	
Warranty	12 months
Printing head	50KM

ACCESSORIES	
Accessories	Data cable, power adaptor, power cord, manual, CD

PACKING	
Individual box	Dimension 240 x 240 x 168 mm (L x W x H), 1 unit/carton
Master carton	Dimension 520 x 260 x 550 mm (L x W x H), 6 unit/carton

OS	
Emulation	TSPL / CPCL / ESC / POS
Driver	Windows / Linux / Mac
SDK	Windows / Android / iOS