

58MM LABEL PRINTER

Model: **KD5808**

MAIN FEATURE

- Carbon free, color free, ink free
- Rich interface, USB + LAN / USB + LAN + BLUETOOTH
- Supports logo download and printing
- Simple installation of drivers and setup software
- Support PDF417, QR code, data matrix



Two-dimensional
code printing



Large font
library



High Definition
Printing



Easy Paper
Design

TECHNICAL SPECIFICATIONS

Print	
Printing Mode	Direct Thermal
Print Speed	Max: 101mm/s
Separation Rate	384 dots/line
Resolution	203 dpi
Print Width	48mm
Port	USB+LAN / USB+LAN+BLUETOOTH

Memory size	
Input Buffer	256kbytes
NV Flash	4M

Typeface	
Font	Alphanumeric; Simplified Chinese; Traditional Chinese; 35 international character sets

Money Case	
DC 12V / 1A	

Sensor	
Print head position detection	Microswitch
Paper Detector	Seam mark detection, missing paper detection, open cover detection

Attachment	
USB cable, power cable, manual	

OS	
Emulation	TSPL, CPCL, ESC/POS
Driver	Windows XP / Vista / Win7 / Win8 / Win10 / Win2000 / Win11 / Android / iOS / Windows
Simulate	ESC/POS

Paper	
Paper Type	Thermal label paper
Paper Thickness	0.06mm~0.19mm
Paper Width	45 / 40 / 35 / 30 / 25 / 20 / 15 / 57mm (Backing paper)
Loading Mode	Wrapper
Roll Dia	50mm (MAX)
Cutter	Tear by hand

Bar Code	
1D	CODE128 / 128M / EAN128 / CODE39 / 39C / CODE93 / EAN13 / EAN13+2 / EAN13+5 / AN8 / EAN8+2 / EAN8+5 / 25 / 25C / CODABAR / POSTNET / UPC-A / UPCA+2 / UPCA+5 / UPC-E / UPC-E+2 / UPC-E+5 / CPOST / MSI / MSI C / PLESSEY / ITF14 / EAN14
2D	PDF417 / QR Code / Data Matrix

Physical Characteristics	
Working Condition	5°C~45°C, 20%~80%RH (no condensation)
Storage Condition	-40°C~55°C, ≤93%RH (40°C)
Dimension	131(D) × 118(W) × 93.3(H) mm
Net Weight	0.45KG
Gross Weight	0.6KG

Power Supply	
Input	AC 100V~240V, 50/60Hz
Exportation	DC 9V / 2.0A

Reliability	
Print Head	50KM
Cutter	No

Package		
Inner Box	190 × 130 × 100 mm (L×W×H)	
Outer Box	605 × 290 × 348 mm (L×W×H)	18 sets per carton