

KD910

4 INCH SHIPPING LABEL PRINTER



High-speed
printing



Two-dimensional
code printing



Big paper roll



Big font

FEATURES

- Automatic induction, positioning test
- Professional wear-resistant print head, designed for printing
- Stable performance, high-speed and clear printing
- It can print continuously for every day.
- Ribbon-free, ribbon-free, ink-free
- Worry-free printing, mobile phones and small programs can print easily.



GENERAL	
Model	KD910
Print Method	Direct Thermal
Resolution	203dpi(Bdots/mm)
Printing Width	108mm
Memory	Input buffer: 2M NV Flash: 4M
Interface	U19+S+U+BT/U+WIFI
Print Speed	152mm/s

GRAPHICS / SYMBOLOGIES	
Character size	Font 0 ~ Font 8
Graphics Processing	Support BMP/PCX/BAS files

FONTS	
Font A	12x24
Font B	9x17
Chinese	GB18030, BIG5 24x24dots
Japanese/Korea	Support
User-defined	Support

BARCODE	
1D	CODE128/128M/EAN128/CODE39/39C/39S/CODE93/EAN13/EAN13+2/EAN13+5/EAN8/EAN8+2/EAN8+5/25/ITF/CODABAR/POSTNET/UPC-A/UPC-E/UPC+5/UPC-A+2/UPC-E+2/UPC-E+5/C-015/COOSTMS/MSIC/PLESSEY / ITF14 / EAN14
2D	PDF417/QRCODE/DATA MATRIX

DETECTION	
Sensors	Thermal sensitive resistance
Paper exists detection	Photoelectric sensor

POWER SUPPLY	
Input	AC 100V~240V 50/60HZ
Output	DC 24V/2.5A

PAPER	
Paper Type	Thermal Receipt Paper/Thermal label paper
Paper Width	25.2~110mm
Paper Thickness	0.06~0.19mm
Roll Inner Diameter	25mm~38mm
Roll Dia	Max. Ø110mm
Paper off	Tear off

PHYSICAL CHARACTERISTICS	
Working Condition	5°C~45°C, 20%~80%RH
Storage Condition	-40°C~55°C, ≤ 93%RH(40°C)
Dimensions	226.5(D)X183(W)X162(H)mm
Weight	Net weight: 2.3 kg Gross weight: 13.8 kg/ctn

RELIABILITY	
Printing head	50KM

ACCESSORIES	
Accessories	data cable, power adaptor, power cord, code, manual, CD

PACKING	
Individual box	Dimension 280 × 255 × 187 mm (LXWXH)unit/box
Master carton	Dimension 525 × 290 × 587 mm (LXWXH) 6units/carton

OS	
Emulation	TSPL(Label model/ ESC/POS/Receipt mode)
Driver	Windows XP/ Win7/Win8 /Win10/Win11
SDK	Android, IOS